

<p>Description</p> <p>Compact Protection Devices which provide MCB overcurrent protection and RCCB earth leakage protection in a single unit.</p> <p>Technical data</p> <p>Temperature: -5°C to 40°C</p> <p>2 poles 127V - 230V</p> <p>Requency 50Hz</p> <p>Specifications:</p> <p>IEC61009-1 6kA</p> <p>IEC60947-2 10kA</p>	<p>Technical data</p> <p>The units are available with Current rating of 6A, 10A, 16A, 20A, 25A, 32A, 40A.</p> <p>The device switches both the phrase and neutral all ratings have 30mA earth leakage protection.</p> <p>The units feature indicators which show whether tripping is due to an overcurrent or earth leakage fault</p>	<p>Mechanical life:</p> <p>20 000 operations</p> <p>Type AC</p> <p>Connection capacity</p> <p>25mm² rigid conductor</p> <p>16mm² flexible conductor</p> <p>Complies with IEC60947-2</p>
--	---	---



Sensitivity IΔn	Breaking capacity	Code 2P	Description	Width in 17.5mm	Pack Q'ty
High sensitivity 30mA	6kA	AD610B	MCB 2P 6kA 10A 30mA	2	6
		AD616B	MCB 2P 6kA 16A 30mA	2	6
		AD620B	MCB 2P 6kA 20A 30mA	2	6
		AD625B	MCB 2P 6kA 25A 30mA	2	6
		AD632B	MCB 2P 6kA 32A 30mA	2	6
		AD640B	MCB 2P 6kA 40A 30mA	2	6