





Description	Breaking capacity	Connection capacity
Protection and control of circuits against overloads and short circuits in domestic, commercial and industrial application.	IEC 60898 6kA IEC 60947-2 10kA NEMA AB-1 22KAIC	(Up to 63A) 25mm ² rigid conductor 16mm ² flexible conductor Complies with IEC60947-2
Technical data	Reference Calibration	Accessories
MUxxxA = type C tripping	Temperature: 30°C Voltage rating: 230/400V Current rating: 2A - 63A	- Auxilliaries contact - Shunt-trips
according the IEC 60898 BSEN 60898	Mechanical endurance: 20 000 operations	
Approval: KEMA - SNI - LMK		

	Current	Cat. Ref	Description	Width in	Pack
	A	C Curve	IEC 60898	17.5mm	Q'ty
	Single Pole				
	6	MU106A	MCB 6kA 1P 6A	1	12
	10	MU110A	MCB 6kA 1P 10A	1	12
	16	MU116A	MCB 6kA 1P 16A	1	12
	20	MU120A	MCB 6kA 1P 20A	1	12
	25	MU125A	MCB 6kA 1P 25A	1	12
	32	MU132A	MCB 6kA 1P 32A	1	12
	40	MU140A	MCB 6kA 1P 40A	1	12
50	MU150A	MCB 6kA 1P 50A	1	12	
63	MU163A	MCB 6kA 1P 63A	1	12	
	Double Poles				
	6	MU206A	MCB 6kA 2P 6A	2	6
	10	MU220A	MCB 6kA 2P 10A	2	6
	16	MU226A	MCB 6kA 2P 16A	2	6
	20	MU220A	MCB 6kA 2P 20A	2	6
	25	MU225A	MCB 6kA 2P 25A	2	6
	32	MU232A	MCB 6kA 2P 32A	2	6
	40	MU240A	MCB 6kA 2P 40A	2	6
50	MU250A	MCB 6kA 2P 50A	2	6	
63	MU263A	MCB 6kA 2P 63A	2	6	
	Triple Poles				
	6	MU306A	MCB 6kA 3P 6A	3	4
	10	MU320A	MCB 6kA 3P 10A	3	4
	16	MU326A	MCB 6kA 3P 16A	3	4
	20	MU320A	MCB 6kA 3P 20A	3	4
	25	MU325A	MCB 6kA 3P 25A	3	4
	32	MU332A	MCB 6kA 3P 32A	3	4
	40	MU340A	MCB 6kA 3P 40A	3	4
50	MU350A	MCB 6kA 3P 50A	3	4	
63	MU363A	MCB 6kA 3P 63A	3	4	
	Four Poles				
	6	MU406A	MCB 6kA 4P 6A	4	3
	10	MU420A	MCB 6kA 4P 10A	4	3
	16	MU426A	MCB 6kA 4P 16A	4	3
	20	MU420A	MCB 6kA 4P 20A	4	3
	25	MU425A	MCB 6kA 4P 25A	4	3
	32	MU432A	MCB 6kA 4P 32A	4	3
	40	MU440A	MCB 6kA 4P 40A	4	3
50	MU450A	MCB 6kA 4P 50A	4	3	
63	MU463A	MCB 6kA 4P 63A	4	3	