





Description	Breaking capacity	Connection capacity
Protection and control of circuits against overloads and short circuits in domestic, commercial and industrial electrical distribution systems.	IEC 60898 10kA	(Up to 63A)
	IEC 60947-2 15kA	25mm ² rigid conductor
	NEMA AB-1 30KAIC	16mm ² flexible conductor
		Complies with IEC60947-2
Technical data	Reference Calibration	Positive Contact Indication
NCxxxA = type C tripping	Temperature: 30°C	Red - Contacts Closed
according the	Voltage rating: 230/400V	Green - Contacts Open
IEC 60898	Current rating: 0.5A - 63A	Accessories
BSEN 60898	Mechanical endurance: 20 000 operations	- Auxilliaries contact
		- Shunt-trips

	Current	Cat. Ref	Description	Width in	Pack
	A	C Curve	IEC 60898	17.5mm	Q'ty
	Single Pole				
	6	NC106A	MCB 10kA 1P 6A	1	12
	10	NC110A	MCB 10kA 1P 10A	1	12
	16	NC116A	MCB 10kA 1P 16A	1	12
	20	NC120A	MCB 10kA 1P 20A	1	12
	25	NC125A	MCB 10kA 1P 25A	1	12
	32	NC132A	MCB 10kA 1P 32A	1	12
	40	NC140A	MCB 10kA 1P 40A	1	12
	50	NC150A	MCB 10kA 1P 50A	1	12
63	NC163A	MCB 10kA 1P 63A	1	12	
	Double Poles				
	6	NC206A	MCB 10kA 2P 6A	2	6
	10	NC220A	MCB 10kA 2P 10A	2	6
	16	NC226A	MCB 10kA 2P 16A	2	6
	20	NC220A	MCB 10kA 2P 20A	2	6
	25	NC225A	MCB 10kA 2P 25A	2	6
	32	NC232A	MCB 10kA 2P 32A	2	6
	40	NC240A	MCB 10kA 2P 40A	2	6
	50	NC250A	MCB 10kA 2P 50A	2	6
63	NC263A	MCB 10kA 2P 63A	2	6	
	Triple Poles				
	6	NC306A	MCB 10kA 3P 6A	3	4
	10	NC320A	MCB 10kA 3P 10A	3	4
	16	NC326A	MCB 10kA 3P 16A	3	4
	20	NC320A	MCB 10kA 3P 20A	3	4
	25	NC325A	MCB 10kA 3P 25A	3	4
	32	NC332A	MCB 10kA 3P 32A	3	4
	40	NC340A	MCB 10kA 3P 40A	3	4
	50	NC350A	MCB 10kA 3P 50A	3	4
63	NC363A	MCB 10kA 3P 63A	3	4	
	Four Poles				
	6	NC406A	MCB 10kA 4P 6A	4	3
	10	NC420A	MCB 10kA 4P 10A	4	3
	16	NC426A	MCB 10kA 4P 16A	4	3
	20	NC420A	MCB 10kA 4P 20A	4	3
	25	NC425A	MCB 10kA 4P 25A	4	3
	32	NC432A	MCB 10kA 4P 32A	4	3
	40	NC440A	MCB 10kA 4P 40A	4	3
	50	NC450A	MCB 10kA 4P 50A	4	3
63	NC463A	MCB 10kA 4P 63A	4	3	